



MR4300

Protects and Maximizes the Performance of Home Theater Systems



Provide protection, filtration and power monitoring for your home theater system

- Nine Protected & filtered Power Outlets
- Exclusive Automatic Voltage Monitoring (AVM)
- Protect or Disconnect Technology
- USB Charging (0.5V / 5V)
- Linear Level 3 Filtration (2 Total Isolated banks) with Dedicated High Current Outlet Bank (4 Outlets)
- Antenna, Cable or Satellite, LAN and TELCO signal protection
- Rotating & Dimmable Media Lights Illuminate Equipment
- 8ft Power Cable with Low Profile Plug
- Rack ears included

MR4300 Protects and Maximizes the Performance of Home Theater Systems



Specifications

Voltage Protection Rating (UL 1449 3rd Edition, 3,000a)	300V
Single Pulse energy Dissipation	1575 Joules
Response time	< 1ns
Nominal discharge Current (UL 1449 3rd Edition)	3,000A
LAN - Jacks	RJ-45
LAN - Compatibility	10/100/1000bt
LAN - Clamping Level	62V ± 6V @ 1 mA
Telco - Fuseless / Auto-Resetting	Yes
Telco - Jacks	RJ-11
Telco - Clamping Level	260V
Coax Protection - Shielded	Yes
Coax - Insertion Loss	< 0.5 db
Coax - HD 1080 i/p Ready	Yes
Coax - Frequency Range	0 MHz - 2.2 GHz
Coax - Clamping Level	75v
Coax - Bidirectional	Yes
Coax - Connections	Female "F", Gold Plated

Other Specifications

Family	MR Series
Line Voltage	120 (Volts)
Number of Outlets	9
Number of Isolated Banks	2
Outlet Descriptions	All 9 outlets filtered, and surge protected. Bank 2 outlets are high current
Rack Mountable	Yes
Rack Ears included	Yes
Font Panel Meter(s)	LED voltmeter
Front Media Light(s)	2 rotating, dimmable media lights
Control	On/Off control to all outlets through front panel power button
Voltage Regulation	No
Compliance	cCSAus
USB Charging	1 front panel USB charger
Low Voltage Trigger	N/A
AC Power Cord	8 ft captive, with low profile plug
Dimensions	17"W x 6"D x 1.75"H, 2.19"H with feet
Weight	6.5 lbs
AC Protection Technology	Protect or Disconnect Automatic Voltage Monitoring L-N, L-G, N-g Protection Modes Thermal Fusing

Under-voltage Shutoff	100 ± 2V
Over-voltage Shutoff	140 ± 4V
Maximum current Rating	15 (Amps)
Initial Clamping Level	200V Peak
Filtration Technology	LIFT
Filtration Rating	Bank1: -70db min. @ 100kHz -65db min. @ 500kHz Max filtration: -80db @ 150kHz Bank 2 - High Current, Low Impedance -50db min. @ 100kHz -60db min. @ 250kHz -45db min. @ 500kHz Max filtration: - 63db @ 250kHz
Signal Line Protection	1 LAN, 1 Tel, 2 Cable/Satellite
length	19.6"
Width	12.1"
Height	8 (Lbs)
Unit of Measure	Each
UPC	050616008938
Master Park Qty	4
Warning	Cancer and Reproductive Harm www.P65Warnings.ca.gov



- Power On / OFF
- Outlet Banks 1 & 2 Indicator LEDES
- On / OFF For Vertical Blue Lights (Blue lights can be illuminated when power is off)
- Safe Power and Filtration Indicator
- Media Lights Control
- Rotatable Media Lights 45 Left or Right
- Front Panel Convenience Outlet
- USB Charger



- 15A Resettable Circuit Breaker
- Ground Lug
- All AC Outlets (Front and Back) Include surge protection and noise filtration
- LAN Surge Protection 1 Pair of RJ-45 IN / OUT Connectors
- TEL Surge Protection 1 Pair of RJ-11 IN / OUT Connectors
- Rack Mountable (Rack ears Sold Separately)
- Coaxial Surge Protection 1 Pair universal IN / OUT Connectors

Niceforyou.com

