



AccuFit Ultra Slim Series

Space may have been called the final frontier, but it isn't always easy to find. All custom installers have had to confront installs that made it difficult if not impossible to install standard in-ceiling speakers. We recognized the problem and came set out to create a solution, the AccuFit Ultra Slim.

Not content to make an ordinary shallow speaker we went to work creating a small masterpiece. The AccuFit Ultra Slim models feature a single dome tweeter surrounded by four 3-inch drivers. Two of which are mid range and the other two are woofers. The use of multiple small drivers with neodymium magnets allow for greater bass response, sound pressure levels and dispersion. The rear of the speaker is completely sealed in a zinc and powder coated steel enclosure. The enclosure not only assures consistent sound quality regardless of placement but also limits sound transfer into adjacent rooms.

With a total depth of only 50 millimeters, just under 2-inches, this speaker will fit in a myriad of different applications. Ultra thin walls, ceilings where drywall has been placed over an existing surface or simply any install with extreme depth restrictions are all situations for which the AccuFit Ultra Slim is a perfect solution.



AccuFit Ultra Slim Three

- (2) 3" Custom Aluminum Cone Woofers
- (2) 3" Custom Aluminum Dome Midrange Drivers
- ¾" Aluminum Dome Tweeter
- Shallow-Depth, Ported, Magnetically Sealed Steel Enclosure
- Timbre-Matched to All Three Series Speakers
- STL (Sound Transmission Loss) Feature: 20dBA
- Sensitivity: 90 dB 1W/1M
- Frequency Response: 90Hz - 20kHz
- Dimensions (Dia x D): 9 1/8" x 2"
mm = (252 x 50)
- Cut-Out Diameter: 8 1/4" (210mm)
- Patent Pending



AccuFit Ultra Slim One

- (2) 3" Custom Polypropylene Cone Woofers
- (2) 3" Custom Aluminum Dome Midrange Drivers
- ¾" Resin Coated Silk Dome Tweeter
- Shallow-Depth, Ported, Magnetically Sealed Steel Enclosure
- Timbre-Matched to All One Series Speakers
- STL (Sound Transmission Loss) Feature: 20dBA
- Sensitivity: 89 dB 1W/1M
- Frequency Response: 90Hz - 20kHz
- Dimensions (Dia x D): 9 1/8" x 1 1/8"
mm = (252 x 50)
- Cut-Out Diameter: 8 1/4" (210mm)
- Patent Pending

* All AccuFit Ultra Slim Speakers come with Limited LIFETIME Warranty

* As we incorporate design improvements, specifications may change without notice



940 Columbia Ave., Riverside CA 92507 • USA (800) 448 0976 Fax (951) 787 8747 International +1 951 787 0543 • www.speakercraft.com