

EL-HR40Remote Control



Multifunction Smart Home Remote

The EL-HR40 Remote Control redefines the remote control experience. It is a full-fledged control interface that lets you answer the front door with video, view surveillance cameras, or communicate with other interfaces using intercom, all using the 3.1" high resolution touchscreen.

With swipe, scroll and touch controls, the HR40 is intuitive to use and provides an unparalleled user experience for control of media, lighting, climate, security, surveillance, and more.

Wirelessly configured, the HR40 can be quickly added to any Nice/ELAN system. Interface templates for popular sources within the Configuration Software enable the HR40 to be personalized, so all customers can experience the most intuitive control for their system.

DESIGNED FOR ELAN CONTROL SYSTEMS



EL-HR40 Multifunction Smart Home Remote

Features

- · Capacitive touch screen
- Back lit buttons
- · Wakes on motion or button press
- Integrated voice control
- · Quick access to number buttons on the touch screen
- Remote finder
- On screen meta-data feedback
- Monitor surveillance cameras from the touchscreen
- Integrated intercom communicate with other Nice/ELAN user interfaces or answer a video doorbell
- Area-based Control for lighting, climate, media, and more
- · Direct IR Control without IR emitter cables
- Wi-Fi connectivity provides extended range
- Magnetic charging base securely holds the remote in place
- · Wireless configuration for simple deployment

DESIGNED FOR ELAN CONTROL SYSTEMS



Compatible with the following Nice/ELAN System Controllers:

- g1
- gSC2
- gSC10
- EL-SC-100
- EL-SC-300

PACKAGE CONTENTS

- Remote control
- Charging base
- · Charging cable
- Power supply
- User manual



Specifications

Touch Screen	LED Backlit Capacitive Touch
Screen Size	3.1" Diagonal / 78.75 mm Ultra Thin Bezel
Illumination	Backlit with Adjustable Brightness Control
Resolution	480 x 800
Viewing Angle	80° (up/down/left/right)
Infrared	40 ft / 12 meters - Line of Sight
Wi-Fi	2.4GHz
Charge Contacts	Gold Plated
Microphone	MEMS, omni-directional, sensitivity: -42dB
Charging Power Requirements	5 V 2.00 A
Remote Dimensions	7.85 x 2 x 0.5 in / 200 x 52 x 14 mm
Remote Weight	6.5 oz / 0.18 kg
Base Dimensions	2.7 x 2.7 x 1.0 in / 70 x 70 x 25 mm
Base Weight	7.5 oz / 0.21 kg

