Interactive Touch Panels

ELAN®

EL-ITP-8-BK
8" Interactive Touch Panel

IV IntelliVision®
AI and Video Analytics for Smart Cameras

IntelliVision face recognition and analytics enable a new level of personalization and control.

EL-ITP-12-WH
12" Interactive Touch Panel

With Voice Control and IntelliVision® Analytics

The EL-ITP-8 and EL-ITP-12 are interactive touch screen interfaces for ELAN controllers. The touch screens are elegantly designed to have a low profile on the wall while providing a rich user experience that is dedicated and always on.

Now with IntelliVision® analytics, these interactive touch screens personalize the user experience through the panel's camera! And using a dual digital MEMS microphone-array that optimizes beam forming and noise cancellation, the ELAN interactive touch screen provides a voice control interface for the ELAN system.

The touch screens wake as the user approaches and displays the award-winning user interface to control all of the home's systems, and a

seven-button fly-out keypad can operate media favorites, trigger lighting scenes, or through installer programmed Event Maps, or control virtually anything connected to the system.

The touch panels are designer friendly as well. By taking advantage of the unique ELAN compatibility with both portrait and landscape user interfaces, it is equally at home in both a horizontal and a vertical orientation. This provides installation flexibility that allows the touch panel to be located in most areas that would accommodate a 2-gang wall plate.

As with all ELAN products, the 8 and 12 inch touch panels are designed to be easy and flexible. It starts with mounting using a standard 2 gang

(US) box, which means no custom bracket to order or stock. The back-box centers with the touch panel making it much easier to place during pre-wire. An included bracket mounts to the standard 2 gang (US) box and the panel simply snaps into place—no special tools needed. The panel locks into place for security and can be removed using the included removal key. The touch panel can be powered locally using a 12VDC power supply (not included) and connected to the controller over Wi-Fi or using power over Ethernet and with a single wire hookup.

- Integrated microphone array extends the voice control interface for an ELAN system

- IntelliVision® video analytics personalizes the user experience through the panel's camera

- Displays high resolution video and provides playback interface for ELAN surveillance

- 8" or 11.6" diagonal viewable area

- LCD capacitive touchscreen

- Contemporary, sleek industrial design

- Edge to edge glass

- Proximity sensor to wake from sleep without touching as hand approaches

- 7 button flyout provides instant access to lighting scenes, favorites or Event Maps

- Mounts into drywall, brick, stone, plaster, and wood, using a standard 2g U.S. junction box

- Portrait or landscape mounting

- Plug and play operation with ELAN Software

- Locally powered (optional)

- Available in white and black bezel

SPECIFICATIONS

Dimensions ITP-8	Overall 8" wide x 5.5" height, 20.33w x 13.98h (cm), mounting depth 1" (2.54cm)
Dimensions ITP-12	Overall 11.68" wide x 7.25" height, 29.67w x 18.40h (cm), mounting depth 1" (2.54cm)
Display	8" diagonal, 11.6" diagonal
Resolution	**ITP-8:** 1920W x 1200H, **ITP-12:** 1920W x 1080H
Microphone	Dual Digital MEMS Microphone-Array
Speaker	Stereo Micro Speaker, 1W
Camera	5 Mega-Pixel CMOS sensor
Network	10/100 Ethernet / 802.11 B/G/N WiFi

CONNECTIONS

Type	LAN/PoE: RJ-45
Power	2 pin Phoenix
USB	USB Type A

POWER REQUIREMENTS

Direct	12 V 1 A
PoE	IEEE 802.3at, (power over Ethernet) 13w maximum draw (@48V $=$ 270 mA max)

INCLUDED IN THE BOX:

(1) EL-ITP-8 or EL-ITP12 Touch Panel
(1) Quick Install Guide
(1) Mounting Bracket
(4) Mounting Screws
(1) DC Power Connector
(1) Panel Removal Key

ELAN®

Your world, made simple.™

www.elanhomesystems.com