

Panamax MD2 products are designed, engineered and manufactured with the highest quality materials and craftsmanship. Protect, maximize performance, and add years of trouble-free use for your valuable home entertainment/office electronic equipment.

COMMON FEATURES FOR ALL MD2s

- Over 40 Years Engineering Experience
- Patented Technology
- · Protect-or-Disconnect Circuitry
- Exceeds UL Safety Standards
- . Thin Profile and Compact in Size
- Surge Protection
- Noise Filtration
- Connected Equipment Longevity
- · Lifetme Product Warranty
- \$100,000 Connected Equipment Warranty













Versatile Outlet Orientation (90 degree angle from one another) to accommodate a variety of plugs.



All MD2s have reversible front cover plates to expose or hide indicator lights from frontal view



Front cover can easily be removed and painted to match any wall color.



Thin Profile to Fit Behind Furnifture and Appliances



MD2 FAMILY 2 AC Outlet, Point-of-Use Protection for Home or Office

Product Features

MD2



Multi-Use AC Surge Protection for **Appliances**

Features:

- 2 AC Outlets
- Protect or Disconnect™ Surge Protection
- EMI/RFI Filtration Circuitry
- Two Diagnostic Lights (LED) Power On/Protection OK and Line Fault

MD2-C



AC & Coaxial Protection for TVs. Plasmas/LCD's, DVD/DVR Players, Cable Modems, HDTV Tuners

Features:

- 2 AC Outlets
- \bullet Protect or Disconnect $^{\text{TM}}$ Surge Protection
- EMI/RFI Filtration Circuitry
- Two Diagnostic Lights
- One Pair of Universal CATV/SAT/ANT Connectors
- 4 ft. Coax Cable Included



One Pair Coax Connectors

MD2-TL





2 In/OutTel/LAN Connectors

AC & Tel/LAN Protection for Computers, DSL Modems, Dial-up Modems, Fax Machines & Printers

Features:

- 2 AC Outlets
- Protect or Disconnect[™] Surge Protection
- EMI/RFI Filtration Circuitry
- Two Diagnostic Lights
- 4 ft. Telephone Cable RJ-11 Included
- 4 ft. LAN Cable RJ-45 Included
- Telephone/ LAN line Protection

MD2-AV





3 In/Out RGB Connectors

AC and RCA Signal Line Surge Protection for Remote Powered AV Equipment and Subwoofers

- 2 AC Outlets
- Protect or Disconnect™ Surge Protection
- EMI/RFI Filtration Circuitry
- Two Diagnostic Lights
- 3 Circuits RCA Input/Outputs
- Module to Deliver Signal from Source Component to MD2-AV to Remote AV Equipment



Extension Module

Specifications

Model:	MD2	MD2-TL	MD2-C	MD2-AV
Protect or Disconnect™ Surge protection	Yes	Yes	Yes	Yes
AC Filtration	50dB (100kHz – 1 MHz)	50dB (100kHz – 1 MHz)	50dB (100kHz – 1 MHz)	50dB (100kHz – 1 MHz)
AC Outlets	2	2	2	2
Cable/ Satellite Protection			1 Pair, Universal 0MHz - 3GHz	
Telephone/LAN line Protection		Telco Clamping Level 260V LAN Clamping Level 60V, 4 Wires Pins 1, 2, 3, & 6		
RCA Line Level Protection				3 Pairs, Signal Line Connectors <0.68dB from 10Hz-6MHz
Removable, Paintable Front-Cover	Yes	Yes	Yes	Yes
Warranties Product	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
Connected Equipment	\$100,000 Limited Lifetime	\$100,000 Limited lifetime	\$100,000 Limited lifetime	\$100,000 Limited Lifetime
Agency Approval c UL) us	Yes	Yes	Yes	Yes
l .				I .

Specifications subject to change due to product upgrades and improvements.

