

# PAS-C854-SUB

## Small Aperture Subwoofer



**Signature**  
SERIES

### **POWERFUL BASS *WITHOUT SACRIFICING SPACE***

Concealed behind the ceiling to deliver rich, detailed sound from a compact 4.75" opening

The PAS-C854-SUB Small Aperture In-Ceiling Subwoofer delivers best-in-class, deep bass performance through a small, finished opening to meet the aesthetic needs of the modern home. Designed to hide the woofer cabinet between ceiling joists and port the low-frequency sound through a small, 4.75" opening in the ceiling. It features a custom 8.27" polypropylene woofer, dual 1 1/2" voice coils, precision tuned port tube and a vinyl wrapped MDF cabinet, mounted to a single joist.

Designed and engineered in the USA, in tandem with the PAS-C355 Small Aperture speaker and PAS-A4100 Amplifier to deliver a complete system, optimized for aesthetics, performance, and flexibility.



# PAS-C854-SUB Small Aperture Subwoofer

## Features


- **8.27" Custom Polypropylene Cone**  
The cone size is maximized based on the cabinet proportions to deliver exceptional performance
- **Dual Voice Coil**  
Easily integrate into existing stereo wiring, or use included shorting bars to impedance match amplifiers when installing multiple subwoofers
- **Analog Filtering Circuits**  
Massive 10 MH Inductor for each voice coil, 1st-order filter, and CR circuit to suppress tube modes—filters out unwanted midrange and high frequencies to optimize woofer performance and reduce resonances, resulting in deep clear bass
- **4.75" Cut-out Size**  
Use a standard hole saw for a quick install into a broad range of materials
- **Simple Mounting**  
Mount cabinet to a single joist. Integrated absorption pads reduce kinetic transmission through the joist




Includes two low-profile, paintable grilles for a round or square finish to match custom recessed lighting, fixtures and ceiling color:



(1) Round  
Low-Profile  
5.25" Grille



(1) Square  
Low-Profile  
5.25" Grille



Includes cut-out template for both grilles.  
*Optional Flush Mount Mudbank available for a near invisible aesthetic. (sold separately)*

### Accessories:

- SC-IC3-PCB | Pre-Construction Bracket
- SC-IC3-FLUSH-ROUND | Round Flush Mount Mudbank
- SC-IC3-FLUSH-SQUARE | Square Flush Mount Mudbank

## Specifications

Woofer Size	8.27"
Woofer Configuration	4th Order Bandpass
Woofer Material	Polypropylene
Hole Cutout Dimensions	4.75"
Power Handling (Watts)	50 - Minimum / 100 - Maximum
Frequency Range	20Hz~300Hz
Impedance	Dual 8Ω Voice Coil
Low-Pass Filtration	Built-In 10mH Filter Per Voice Coil Optimize Bass, Removes High Frequencies
Sensitivity	71 dB
Weight	14.1 lb
Depth Behind Wall	7.125"
Dimensions	Cabinet with Port Tube: 25.188" Length, 12" Width, 7.125" Depth Finished Grille Dimensions: 5.25"
Shipping Dimensions	12" x 36" x 15" (302 x 907 x 874 mm)
Shipping Weight	34.4 lbs

Nice

©2024 Nice North America LLC. Proficient is a registered trademark of Nice North America LLC. All rights reserved.

PROFICIENT  
AUDIO a Nice brand

proficientaudio.com